

TERMS AND CONDITIONS OF SALE

- MINIMUM ORDER:** One piece!
- DROP SHIPMENTS:** CBI is pleased to provide drop shipment service for your customers. However, a handling charge will apply. Signatures will be required
- CUSTOM ORDERS:** CBI will build to your exact requirements. Custom work will require written approval and/or drawings. Quotes and delivery information are usually available the same day. A deposit of a portion up to the full amount may be required. All deposits are non-refundable once production has begun, or custom parts have been ordered.
- PRIVATE PACK:** CBI offers private label / custom packaging to our dealers and distributors. Minimum orders apply, and custom packaging materials must be prepaid by the customer.
- IMPRINTING:** Custom imprinting on heatshrink is available on a minimum order of 25 pieces. There is a per piece Print charge to each cable for this service. Begin Model # with "P-"
- RETAIL PRICE:** Retail prices contained within this catalog are suggested only, and are meant as a guideline for the dealer. Restrictions may apply for national ads and the internet.
- PAYMENT:**
- Prepay Note: All New customers must complete A New Dealer Application
 - COD Cash / Certified Funds
 - COD Company Check - Requires approval of completed New Account application. A NSF fee will apply to all returned checks. Customer is liable for any and all reasonable collection fees on unpaid checks and past due open accounts.
 - Credit Card - Visa, MC, Amex, Discover - Requires cardholder's signature on file. CBI keeps all customer information confidential. A processing fee may apply.
 - Third party Credit Cards will not be accepted.
 - Open Account - Net 30 days - Requires approval of completed Credit application.
- WARRANTY:**
- CONSUMER: Standard cables are guaranteed for a period of 10 years against defects in material and workmanship. Warranty items may be returned prepaid to the factory without prior authorization. Proof of purchase must be enclosed with a description of the problem
- DEALER: Defective standard cables may be returned prepaid to the factory, and will be replaced with new cables on your next order. Some items may be repaired instead at our option. Abused products will be excluded from this guarantee.
- RETURNS:** Prior authorization is required. Call with any problem. All standard returns for credit are subject to a 20% restocking fee. All custom products are non-returnable and non-refundable.
- SHIPPING:**
- All orders are F.O.B. from the factory in Oriskany, NY. CBI will choose UPS or FedEx Ground unless specified. Other options are FedEx, Postal, and common carrier truck (required for 150+ lbs).
Customer is responsible for all additional UPS charges. Residential delivery, refusals, Incorrect addresses, etc.
- RUSH ORDERS:** Expedited orders are CBI's specialty. However, when additional production or shipping costs are incurred by CBI on rushed orders, they will be passed on to the customer as an expedite fee. You will be advised of any such fees before the order is processed.
- LIABILITY:** All prices and specifications subject to change without notice. CBI will not be liable under any circumstances for consequential, incidental, special, or exemplary damages. CBI's liability will be limited to the repair or replacement of a defective product.

All Prices and Specifications Subject to Change Without Notice

For the Latest Prices and Terms, see our Website www.cbicables.com

Ultimate Series The Best at Any Price

Ultimate

CBI ULT-1 "Ultimate" 18 Gauge with 95% DUAL Spiral Shield
 G&H Show Saver USA 1/4" - OFC Solid Shaft / Tip
Double Heat Shrink - Over & Under Barrel
 Distinctive Look - The Name Says it All - Ultimate Performance
 "The Original ULTIMATE Guitar Cable, at an Incredible Price"

Model	Length	Retail
ULT-	3	20.50
	6	22.00
	10	25.00
	15	30.00
	18	32.00
	20	34.00
	25	38.50
G&H Rightfoot Rt Angle - OFC Shaft / Tip	-1R	+4.00

Ultimate NPX

CBI ULT-1 "Ultimate" 18 Gauge with 95% DUAL Spiral Shield
Neutrik NP2X 1/4" Compression Connectors
 Maximum Durability - Cleanest Sound - Professional Look

Model	Length	Retail
ULTNPX-	10	26.50
	15	30.50
	18	33.50
	20	35.00
	25	39.50
Neutrik NP2RCS Slim Line Rt, Angle	-1R	+4.00

Ultimate BASS Gold

CBI ULT-1 "Ultimate" 18 Gauge with 95% DUAL Spiral Shield
100% Gold plated G&H USA 1/4" - OFC Solid Shaft / Tip
 Metallic Gold Logo on Black Shrink - Very Classy Look
 All Ultimate Series Excel at Transporting Your Full Range of Tones

Model	Length	Retail
ULTBG-	10	26.50
	15	30.50
	18	33.50
	20	35.00
	25	39.50
G&H 100% Gold Plated Rightfoot Rt Angle	-1R	+6.00

Ultimate Gold Rush

CBI ULT-1 "Ultimate" 18 Gauge with 95% DUAL Spiral Shield
 100% Gold plated G&H USA 1/4" - OFC Solid Copper Shaft
Popular "Gold Rush" Designer Black Cloth Pattern
 Beautiful Looking - Gold Logo Matches Cloth & Connector

Model	Length	Retail
ULTGR-	10	34.00
	15	41.00
	18	43.50
	20	46.50
	25	53.50
G&H 100% Gold Plated Rightfoot Rt Angle	-1R	+6.00

Whisper Classic Double Heat Shrink

Whisper Classic

CBI 20 Gauge Instrument Wire
 Neutrik Nickel 1/4" Connectors - Hand Soldered
Double Heat Shrink - Over & Under Barrel
 Traditional Black Cable with Blue Shrink
 A Best Seller for over 20 years

Model	Length	Retail
W-	3	11.50
	6	12.50
	10	14.50
	15	16.50
	18	17.50
	20	19.00
	25	22.00
C-226 Nickel 1/4" Barrel Style Rt Angle	-1R	+3.00

Prism Series Designer Patterns

Prism Classic - Vintage Cloth

CBI 20 Gauge Instrument Wire
 G&H Show Saver USA 1/4" - OFC Solid Shaft / Tip
 Nylon CBI Designer Cloth Overbraid - Durable, "No Fray"
Assort or Order your patterns by Number!
 6 NEW Attractive Patterns to Choose from!

Model	Length	Retail
P-	3	17.00
	6	19.50
	10	22.50
	15	26.50
	18	29.00
	20	30.50
	25	34.50
		+4.00
		+10.00
		+5.00
		+5.00
		+5.00

Options:

- G&H Rightfoot Rt Angle 1/4" -1R
- Natural Real Wood Barrels, ea. -1W
- Whisper Double Heat Shrink WPRISM-
- G&H Gold Showsaver 1/4" -GOLD
- "No POPS" G&H Quiet Plug -QUIET

Prism Neutrik

CBI 20 Gauge Instrument Wire
 Neutrik Nickel 1/4" Connector - Very Reliable
 Nylon CBI Designer Cloth Overbraid - Durable, "No Fray"
Assort or Order your patterns by Number!
 C-226 Nickel 1/4" Barrel Style Rt Angle

Model	Length	Retail
PN-	10	20.00
	15	24.50
	18	27.00
	20	28.50
	25	32.50
		+3.00

Gold Rush Metallic Cloth

Gold Rush

CBI 20 Gauge Instrument Wire
 100% Gold Plated G&H Show Saver 1/4"
 Black & Gold Metallic Cloth Jacket - 9 Stunning Patterns
 Sure to Brighten up Any Cable Display!
 G&H 100% Gold Plated Rt Angle

Model	Length	Retail
GR-	10	27.00
	15	31.00
	18	33.50
	20	35.00
	25	39.00
		+6.00

Rock Series

Mesh Ultra Flex

CBI 20 Gauge Instrument Wire - 8 Colors
 G&H Show Saver USA 1/4" - OFC Solid Copper Shaft
Options Same as Prism - See above
 Rugged Monofilament Covering Redefines "Durable Jacket"

Model	Length	Retail
ROCK-	10	22.50
	15	26.00
	18	28.50
	20	30.00
	25	34.00

Black Rose
 Copperhead

PHANTOM
 White Lightning

Lounge Lizard
 Stinger

GA1 Series

GA1 - Standard

Our #1 Selling Cable for 25 Years!

CBI 20 Gauge Instrument Wire, Std Blk or Colors

Neutrik Nickel 1/4" Connectors

Single Shrink under Barrel for Reinforcement

Optional Shrink Colors - Black is Standard

Red, Blu, Pur, Grn, Org, Gry, Yel

Optional GA Series Cable Colors - Black is Std.

Red, Blu, Pur, Grn, Org, Gry, Yel

Options: C-226 Barrel Style Rt Angle
100% Gold Plated Neutrik 1/4"

Model	Length	Retail
GA1-	1	8.50
	3	9.00
	6	10.50
	10	12.00
	15	14.00
	18	15.00
	20	16.00
	25	18.50
	30	20.50
	-1R	+3.00
	-GOLD	+5.00

GA1B - G&H

CBI 20 Gauge Instrument Wire, Upgraded 1/4"

G&H Show Saver USA 1/4" - OFC Solid Shaft / Tip

Single Shrink under Barrel for Reinforcement

The "ALL AMERICAN" CABLE

Options: G&H Rightfoot Solid 1/4" RA
G&H Quiet Plug "No Pops"

Model	Length	Retail
GA1B-	3	12.50
	6	13.50
	10	14.50
	15	16.50
	18	18.00
	20	19.50
	25	21.00
	-1R	+4.00
	-QUIET	+7.00

GA1S - Switchcraft

CBI 20 Gauge Instrument Wire

Switchcraft Nickel 1/4" - The Traditional Standard

Single Shrink under Barrel for Reinforcement

Options: S-226 Barrel Style Rt Angle
S-181 Silent Plug - Button

Model	Length	Retail
GA1S-	10	14.00
	15	15.50
	18	17.50
	20	18.50
	25	20.00
	-1R	+4.00
	-SILENT	+10.00

GA1NPX - Compression

CBI 20 Gauge Instrument Wire

Neutrik NP2X 1/4" Compression Connectors

Slim Line Connector Fits Most Instruments

Options: New! Neutrik NP Series Silent
Neutrik NP2RCS Slim Line RA

Model	Length	Retail
GA1NPX-	10	20.00
	15	22.00
	18	23.50
	20	24.50
	25	26.50
	Call	
	-1R	+4.00

GA1Q - Quad Guitar

CBI Studio Quad Wire - 4 x 24ga Conductors - 95% Braided Shield

Extremely Limp and Flexible - Low Capacitance - Wired for Best Sound

Neutrik Nickel 1/4" Connectors - Single Shrink under Barrel - Options as GA1 above

Model	Length	Retail
GA1Q-	10	19.00
	15	22.50
	18	24.50
	20	26.00

Artist Series

Artist Gold

CBI A-20 Artist 20 Gauge Black Instrument Wire
 Gold Plated 1/4" - Best Contact
 Single Shrink Under Barrel For Reinforcement

Option: C-226G Gold Barrel Style Rt Angle

Model	Length	Retail
AG -	3	12.00
	6	12.50
	10	14.00
	15	16.00
	18	17.00
	20	17.50
	25	19.50
-1R		+4.00

Artist Hot Shrink

CBI Artist 20 Gauge Black Inst. Wire
 Nickel 1/4" Connectors - Hand Soldered
Double Heat Shrink - Over & Under Barrel
 Shrink Colors - Black is Standard or Assort:
 Red, Blu, Pur, Grn, Org, Gry, Yel

Option: C-226 Barrel Style Rt Angle

Model	Length	Retail
AHS -	3	9.50
	6	10.00
	10	11.50
	15	13.50
	18	14.50
	20	15.00
	25	16.50
-1R		+3.00

Artist

24 Gauge Black Instrument Wire
 Nickel 1/4" Connectors - Hand Soldered
 An Excellent Basic Cable - at a Great Price!
Only Available in Listed Lengths - No options

Model	Length	Retail
A -	3	7.00
	6	7.50
	10	8.50
	15	10.00
	20	11.50

Specialty Instrument Cables

*"Don't See What You're
 Looking For?
 Give us a Call!"*

GA4 - 1/8" Mono

CBI 20 Gauge Instrument Wire - Shrink Over 1/8" Barrel
 1/8" Mono - 1/4" Mono
 1/8" Mono - 1/8" Mono

Select	Length	Retail
GA4 - GA4M -	6	12.50
	10	14.50
	15	17.00
	20	19.50

SNG - TRS to TS - Gibson Style

Wired Tip + Ring to Tip for Stereo Instrument Applications
 Belden / CBI 22ga Wire - Neutrik 1/4" Connectors - Top Quality

Model	Length	Retail
SNG -	10	18.50
	15	21.50
	20	24.50

Pedal Patch

20 Gauge Instrument Wire, Blk or Assort Colors
 C-228 Flat Style Rt Angles - Hand Soldered
Only Available in Sizes Listed
 Bulk Packed, Professional Patch Cables

Also - Packaged. Molded, Colored 8 Pks

Professional	Retail
RA-6IN	6.50
RA-8IN	6.50
RA-12IN	7.00
RA8-100PK	650.00
Packaged Molded	Retail
CB2-8RA	15.00

Solution Boxes

Direct Boxes

Passive Audio Transformer - Inst. to Bal. Line
 1/4" Input, Direct 1/4" Out, Male XLR Iso Output
 14ga Steel Box, Optional Ground Lift Switch

Splitter / Combiner

XLR Input to Iso and Direct XLR Output
 Splitter Fem - 2 M Out, Combiner 2 Fem In - Male

Model	Retail
DB	55.00
DBGL	60.00
SPLITTER	60.00
COMBINER	60.00

Upgrade Transformer	Model
Neutrik NTE Series	-NTE
Neutrik NTM Studio	-NTM

MIDI Cables

MIDI - Standard

CBI ML2 24 Gauge Wire - Serve Shield - Very Flexible
 Neutrik 5 Pin Din Male Connectors - All Metal, Hand Soldered
 Cable Colors: Black, Red, Blue, Purple, Yellow and Green
 3 Pins Wired for Standard MIDI Applications

Option: Female 5 Pin DIN

Model	Length	Retail
MIDI-	3	11.50
	6	12.50
	10	14.00
	15	15.00
	20	17.50
-1F		+6.00

MIDIQ - 5 Pins Wired

CBI Studio Quad Wire - 95% Braided Shield - Flexible - Best Quality MIDI Cable
 Neutrik 5 Pin Din Male Connectors - All Pins Wired

A Top Quality, All Purpose MIDI or Control Cable

Model	Length	Retail
MIDIQ-	3	18.00
	6	20.00
	10	22.00
	15	25.00
	20	27.50

Control & Intercom Cables

Intercom / DIN / XLR

Belden Wire, Neutrik / Switchcraft, Wired Pin-Pin

- 6 Pin XLR "NEUTRIK" Style (Telex)
- 6 Pin XLR, "SWTCHCRFT" Style (Clear-Com)
- 7 Pin DIN, Male - Male, Pin 1 Shield
- 8 Pin DIN - Std size, M - M
- 8 Pin MINI-DIN - B9539 Wire, M - M
- 7 Pin XLR Cable, M - F, Pin 1 Shield

Specify Model	Length	Retail
	3	57.50
	6	61.00
XCC6-	10	65.00
XCC6S-	20	77.00
MCC7-	30	88.00
MCC8-	50	110.00
MCC8M-	100	167.00
XCC7-		+10.00

13 Pin DIN - Roland

Belden Black Flexible 100% Shielded 24ga Wire
 13 Pin DIN Connectors - For Use with Roland Equipment
 Other Custom Control Cables - Any Length Available - Call for Quote

Model	Length	Retail
MCC13-	10	65.00
	20	77.00
	30	88.00
	50	110.00

YM - Mono 1/4" / RCA

For Longer Lengths than 10ft
Consider a Custom MT2 / IS1 Snake
To Meet your Y-Cable Requirements
See Page 24

Single	To Dual	Model - Length	Retail
Male 1/4"	Male 1/4"	YM201-1	15.00
Male 1/4"	Female 1/4"	YM202-1	31.50
Female 1/4"	Male 1/4"	YM203-1	21.50
Female 1/4"	Female 1/4"	YM204-1	40.00
Male 1/4"	Male RCA	YM205-1	14.50
Male 1/4"	Female RCA	YM206-1	14.50
Female 1/4"	Male RCA	YM207-1	22.50
Female 1/4"	Female RCA	YM208-1	22.50
Male RCA	Male RCA	YM209-1	16.50
Male RCA	Female RCA	YM210-1	16.50
Female RCA	Male RCA	YM211-1	16.50
Female RCA	Female RCA	YM212-1	16.50

YS - Stereo 1/4" / Insert

CBI Professional Y Cables are Made with
Top Components such as Belden Wire,
Neutrik and Switchcraft Connectors.

Belden 1503A is Standard Throughout

Available upon Request:
CBI MINIFLEX - Flexible Bk 24ga - Spiral Shield
Belden 8451 22ga Extra Thin - Foil Shield

Single	To Dual	Model - Length	Retail
Male 1/4" TRS	Male 1/4" Mono	YS301-1	15.00
Male 1/4" TRS	Female 1/4" Mono	YS302-1	31.50
Female 1/4" TRS	Male 1/4" Mono	YS303-1	24.50
Female 1/4" TRS	Female 1/4" Mono	YS304-1	42.50
Male 1/4" TRS	Male TRS	YS305-1	17.50
Male 1/4" TRS	Female TRS	YS306-1	37.50
Female 1/4" TRS	Male TRS	YS307-1	26.00
Female 1/4" TRS	Female TRS	YS308-1	49.00
Male 1/4" TRS	Male RCA	YS309-1	15.00
Male 1/4" TRS	Female RCA	YS310-1	15.00
Male 1/4" TRS	Male XLR, Bal.	YS311B-1	21.00
Male 1/4" TRS	Male XLR, Insert	YS311S-1	21.00
Male 1/4" TRS	Fem XLR, Bal.	YS312B-1	21.00
Male 1/4" TRS	Female XLR, Insert	YS312S-1	21.00
Male 1/4" TRS	M +F XLR, Bal.	YS313B-1	21.00
Male 1/4" TRS	M +F XLR, Insert	YS313S-1	21.00
Female 1/4" TRS	Male RCA	YS314-1	27.00

YX - XLR Y and "Z"

Single	To Dual	Model - Length	Retail
Male XLR	Male XLR	YX401-1	22.50
Male XLR	Female XLR	YX402-1	22.50
Female XLR	Male XLR	YX403-1	22.50
Female XLR	Female XLR	YX404-1	22.50
Male + Fem XLR	Male + Fem XLR	ZX-1	32.50

MY - 1/8" TRS

MP3 / IPOD / CD Cables
(for longer Runs, See IS1 page 24)

Single	To Dual	Model - Length	Retail
Male 1/8" TRS	Male 1/4" Mono	MY501-1	16.50
Male 1/8" TRS	Female 1/4" Mono	MY502-1	35.00
Male 1/8" TRS	Male 1/4" TRS	MY503-1	19.00
Male 1/8" TRS	Female 1/4" TRS	MY504-1	41.50
Male 1/8" TRS	Male RCA	MY505-1	17.50
Male 1/8" TRS	Female RCA	MY506-1	17.50
Male 1/8" TRS	Male XLR, Bal.	MY507B-1	25.00
Male 1/8" TRS	Male XLR, Insert	MY507S-1	25.00
Male 1/8" TRS	Female XLR, Bal.	MY508B-1	25.00
Male 1/8" TRS	Female XLR, Insert	MY508S-1	25.00
Male 1/8" TRS	M +F XLR, Bal.	MY509B-1	25.00
Male 1/8" TRS	M +F XLR, Insert	MY509S-1	25.00

SGY Series

Professional Stereo Guitar Y

CBI / Belden Wire, Branched Left & Right at Fully Protected Junction - Flexible & Durable
Stereo 1/4" to 2 Mono Leads - All Neutrik 1/4" Connectors - Single Shrink

Model - Lengths	Retail
SGY10+5	35.00
SGY15+5	40.00
SGY20+5	45.00
	+6.00
	+10.00
Call for	+7.00
Other	+5.00
Lengths	+5.00 /ft

Options: G&H Rightfoot Rt Angle TRS 1/4"
Neutrik NPX Series Compression 1/4"
Whisper Double Heat Shrink
G&H / Neutrik Gold 1/4"'s
Studio Quad or Ultimate Wire

-1R
-NPX
-WSGY-
-GOLD
-QUAD or -ULT

The Best Guitars
Deserve the Best Cables

ML Series

Low Impedance

ML Ultimate - Pro Sound

CBI / Belden MLU "Ultimate" 20 Ga Wire - Braided Shield
 Neutrik "X" Series XLR Connectors - 100% Strain Relief
 Cable Colors: Blk, Red, Blu, Pur, Grn, Org, Yel, Wht

The Definitive 'Tour Grade' Pro Sound Mic Cable

ML Ultimate Colors

Options below apply to MLU, MLNQ, and MLN

Options:

Rt. Angle XLR - Fem or Male
 Black Barrel Neutrik XLR's
 Neutrik Black & Gold XLR's
 Colored Boots - 8 Colors

-F(M)R	+10.00
-BAG	+2.50
-GOLD	+7.00
-BSX	+2.50

Model	Length	Retail
MLU-	3	18.50
	6	20.50
	10	23.50
	15	26.50
	20	29.50
	25	32.50
	30	36.50
	50	51.50
	100	90.00

MLNQ - Studio Quad

CBI Studio Quad - 4 x 24ga Conductors - 95% Braided Shield
 Neutrik "X" Series XLR Connectors - 100% Strain Relief
 Wired for Common Mode Rejection at Each Pin

Belden Brilliance 1192A
Mogami Neglex Quad

Model	Length	Retail
MLNQ-	10	22.50
	20	27.50
	25	30.00
	30	33.50
	50	46.50
	100	80.00

MLN - Performer Series

Our #1 Selling Mic Cable! - Professional Grade

CBI/Belden 22 Gauge Mic Wire - Very Flexible & Durable
 Neutrik X Series XLR Connectors - 100% Strain Relief

Great Balance of Durability, Flexibility, and Sound
Options - See ML Ultimate Above

Variations:

Switchcraft XLR's **MLS-**
 Amphenol 3 Pin Screw Type **MLNA3-**
 Amphenol 4 Pin Screw Type **MLNA4-**
 Rotary On/Off Switch on Female **MLNS-**

Model	Length	Retail
MLN-	3	16.00
	6	18.00
	10	20.50
	15	24.00
	20	27.00
	25	30.00
	30	33.00
	50	47.50
	75	65.00
	100	82.50

ML2

CBI 24 Gauge Balanced Wire - Very Flexible - Made in USA
 CBI Nickel XLR's - Hand Soldered in our NY Production Facility
 Cable Colors: Blk, Red, Blu, Pur, Yel, and Grn

A Trouble Free, Basic Microphone Cable

From our CB2 Line of Quality Import Cables:
Economical / Promotional Cable MLC-20ft

Model	Length	Retail
ML2-	3	12.50
	6	13.50
	10	15.00
	15	16.50
	20	17.50
	25	19.50
	50	30.00

MH Series High Impedance

MH - Professional

CBI 20 Gauge Inst Wire - Shrink under Mono 1/4"

Female XLR to Male 1/4" - Pin 3 Hot - Unbalanced

All Neutrik Connectors - Top Quality High Z Mic Cable

Pin 3 Hot, Male XLR

Variations: **Pin 2 Hot, Female XLR**

Pin 2 Hot, Male XLR

Options: S-2501 Screw Ring, Single

Amphenol 3 Pin w/ Ring

Amphenol 4 Pin w/ Ring

Model	Length	Retail
MH-	3	12.50
	6	13.50
	10	15.00
	15	17.00
MHM-	20	19.00
MHV-	25	21.00
MHVM-	30	22.50
	50	31.50
MS-		+5.00
MHA3-		+18.00
MHA4-		+20.00

MH2 - Basic

CBI 24 Gauge Instrument Wire - Black

CBI Nickel C-XLRs - Nickel 1/4" - Quality High-Z Mic Cable

Female XLR to Male 1/4" - Pin 3 Hot - Unbalanced

Pin 3 Hot, Male XLR

Variations: **Pin 2 Hot, Female XLR**

Pin 2 Hot, Male XLR

Model	Length	Retail
MH2-	3	10.00
	6	11.00
	10	12.50
	15	14.50
MH2M-	20	16.00
MH2V-	25	18.00
MH2VM-	30	19.50

MH Prism

CBI 20 Gauge Instrument Wire with Vintage Cloth

All Neutrik Connectors - Shrink under Mono 1/4"

Nylon CBI Designer Overbraid - Durable, "No Fray"

Assort or Order your patterns by Number!

See Page 4 for More Details - Options Same as MH

Model	Length	Retail
MHP-	6	21.00
	10	24.00
	15	27.50
	20	32.00
	25	36.00
	30	40.00

Low-High Z Transformers

Low-High Pro Cable

Belden 22 Gauge Balanced Wire -Flexible & Durable

Neutrik Female XLR - T10AA 1/4" Transformer Connector

For DI Boxes, See Page 8

Male XLR for Direct High-Z Patching

into Balanced Inputs, Snakes, or Consoles

Model	Length	Retail
MHL-	3	56.50
	10	61.00
	20	67.50
	25	70.00
MHLM-	30	73.00
	50	80.00
	100	92.50

Low-High Adapter

Transforms Low-Z XLR Signals to High-Z 1/4"

All Metal Inline Adapter - Packaged for Retail

Model	Retail
LTC	20.00
LTC-12PK	240.00

Balanced Line - TRS

BL Ultimate - Pro Sound

Belden/CBI MLU "Ultimate" 20 Ga w/ Braided Shld

Neutrik Nickel 1/4" TRS - TRS Male

Neutrik TRS - NC3FX Fem XLR

Neutrik TRS - NC3MX Male XLR

Blk Std, Also Available in MLU Cable Colors on Page 11

The Ultimate Cable for Live Sound Patching

Neutrik NP3X TRS Compression Connector

Specify	Length	Retail
	3	20.00
	10	23.50
BLUA-	20	29.50
BLUB-	25	32.50
BLUC-	30	36.50
	50	51.50
	100	90.00
-NPX	(EACH)	+5.00

BL - Standard

Belden/CBI 22 Ga Balanced Wire - Top Seller

Neutrik Nickel 1/4" TRS - TRS Male

Neutrik TRS - NC3FX Fem XLR

Neutrik TRS - NC3MX Male XLR

Options: Belden 1503A Thin Wire, Colors
Belden 8451 Ultrathin - Great for Racks

1/4" TRS Ext. NJ3FC6 Fem Locking

1/4" TRS Ext. S-131 Fem

1/8" Male TRS to 1/4" TRS

1/8" Male TRS to XLR Fem (Male)

1/8" Male TRS to 1/8" TRS

Specify	Length	Retail
	3	16.00
	6	18.00
BLA-	10	21.00
BLB-	15	24.00
BLC-	20	27.00
	25	30.00
-1503	30	33.00
-8451	50	47.50
HXN-		+7.00
HXS-		+7.00
BLAM-		+1.50
BLB(C)M-		+1.50
BLMM-		+2.50

BL2 - Basic

CBI 24ga Balanced Wire - Flexible - Black

Nickel 1/4" TRS - TRS Male

Nickel 1/4" TRS - C-XLR Female

Nickel 1/4" TRS - C-XLR Male

Specify	Length	Retail
	3	15.50
	6	17.00
BL2A-	10	19.50
BL2B-	15	22.00
BL2C-	20	24.50

Unbalanced Line - RCA

GA5 Series RCA Cables

CBI 20 Gauge Instrument Wire

Neutrik RCA Male - 1/4" Male

Neutrik RCA Male - RCA Male

Specify	Length	Retail
	3	9.50
	6	10.50
GA5-	10	12.00
GA5P-	15	13.50
	20	15.50
	25	17.50
-PAIR	DOUBLE	+ 5.00

RCA to XLR Cables

CBI 20 Gauge Instrument Wire, Neutrik RCA's

RCA Male - Female XLR, Pin 3 Hot

RCA Male - Male XLR, Pin 3 Hot

RCA Male - Female XLR, Pin 2 Hot

RCA Male - Male XLR, Pin 2 Hot

Specify	Length	Retail
	3	13.50
	6	14.50
GA5F-	10	16.50
GA5M-	15	18.00
GA5FV-	20	19.50
GA5MV-	25	22.00

SC Series

16 Gauge

CBI Heavy Duty 16 Gauge Unshielded Round - Flex Jacket
Neutrik Large Hole 1/4" Male Connectors

Labeled "CBI 16 Gauge Power Series" - Blue Stripe

Options: C-MDP Banana Plug

Model	Length	Retail
SC16-	3	14.50
	6	16.00
	10	19.50
	15	21.50
	20	23.00
	25	27.00
	30	29.00
	50	42.50
-1M		+3.00

14 Gauge

CBI Heavy Duty 14 Gauge Unshielded Round - Flex Jacket
C-184 High Quality Large Barrel 1/4" Connectors

Labeled "CBI 14 Gauge Power Series" - Yellow Stripe

Option: C-MDP Banana Plug

Model	Length	Retail
SC14-	3	18.00
	6	19.00
	10	22.50
	15	26.50
	20	30.00
	25	34.00
	30	37.50
	50	55.00
	100	93.50
-1M		+3.00

12 Gauge

CBI Heavy Duty 12 Gauge Unshielded Round - Flex Jacket
C-184 High Quality Large Barrel 1/4" Connectors

Labeled "CBI 12 Gauge Power Series" - White Stripe

Options: C-MDP Banana Plug
G&H "USA" Midsize 1/4"

Model	Length	Retail
SC12-	6	24.50
	10	26.50
	15	32.00
	20	37.00
	25	41.50
	30	46.50
	50	70.00
	100	127.50
-1M		+3.00
SCG12-		+5.00

10 Gauge

CBI Heavy Duty 10 Gauge Unshielded Round - Flex Jacket
G&H Megafoot 1/4" Connectors - Solid OFC Tip / Shaft
Labeled "CBI 10 Gauge Power Series" - Red Stripe

Option: G&H "BOSS" MDP

Model	Length	Retail
SC10-	6	28.00
	20	46.50
	25	53.50
	50	86.50
	100	150.00
-1G		+3.00

Banana Adapter Cable

CBI Power Series Heavy Duty 16 Ga Round Wire
Jumbo Female 1/4" - C-MDP Banana Plug

Options: 14 Gauge Wire
12 Gauge Wire

Model	Length	Retail
Z7-	1	25.00
-14-	3	26.50
-12-	6	27.50

Speaker Cables

16 Gauge - Black

CBI Commercial 16ga Unshielded Round - Black Jacket
 Nickel 1/4" Male Connectors
 Economical Light Duty Speaker Cable

C-MDP Banana Plug

Model	Length	Retail
SRB16-	3	10.00
	10	12.50
	20	15.50
	25	16.50
	30	17.50
	50	22.50
-1M		+3.00

14 Gauge - Clear

CBI 14 Gauge Clear Jacketed Wire - Very Flexible
 Black Identification Ground Stripe
 Nickel 1/4" Male Connectors

C-MDP Banana Plug

Model	Length	Retail
SCZ14-	3	9.50
	10	11.50
	20	16.00
	25	18.50
	30	20.50
	50	29.00
-1M		+3.00

12ga Clear Pro - 262 Strands

CBI Premium Parallel 12 Gauge - Thick Clear PVC Jacket
 Rope Style Ultra Fine Stranding -Extremely Flexible
 Red Identification Ground Stripe
 G&H 1/4" OFC Megafoot Connectors - The Most Durable
 Perfect for High End Audio - Great Look and Performance

G&H "BOSS" MDP

Model	Length	Retail
MON12-	3	21.00
	10	26.50
	20	35.00
	25	39.50
	30	43.50
	50	60.00
	100	100.00
-1G		+3.00

Speakon Y Cables

CBI MCS Series Pro Speaker Wire - Neurik NL4FX Speakons
 2 Pole (1+,1-) Duplicated to TWO 2 Pole (1+,1-)
 4 Pole (1+,1-)(2+,2-) Split to TWO 2 Pole (Both 1+, 1-)
 4 Pole (1+,1-)(2+,2-) Duplicated to TWO 4 Pole

Replace NL4FX with Switchcraft MALE

Model - Length	Retail
SNNY22-1	61.50
SNNY42-1	66.50
SNNY44-1	69.00
-1M	+10.00

Speakon - 1/4" Adapter Cable

CBI Power Series Heavy Duty 16 Ga Round Wire

Jumbo Female 1/4" - NL2FC

Options: 14 Gauge Wire
 12 Gauge Wire

Model	Length	Retail
SNNZ-	1	27.50
-14-	3	29.00
-12-	6	30.00

Speakon - 1/4" Adapter

Solid Adapter - Female 1/4" to NL4FC
 Turns Any Standard Speaker Cable into Speakon

Model	Retail
NA4LJ	14.50
NA4LJ-25pk	362.50

2 Pole Wired 1+ 1-

16 Gauge

CBI SC-16 Power Series 16 Gauge - Round Flexible
Neutrik Speakon NL4FX Connectors
Built to Spec then Soldered for Maximum Durability

Options:

NL2FC - NL2FC 2 Pole Connectors
NL4FX - MDP Banana
NL4FX - G&H Bigfoot 1/4"
NLT4FX - NLT4FX PRO METAL

Model	Length	Retail
SNN162-	3	32.50
	10	36.50
	20	41.00
	25	43.50
	30	46.50
	50	56.50
SNN2*-		-4.00
SNNP*-		-4.00
SNNQ*-		-4.00
SNNT*-		+10.00

14 Gauge

CBI SC-14 Power Series 14 Gauge - Round Flexible
Neutrik Speakon NL4FX Connectors
Built to Spec then Soldered for Maximum Durability

Options Same as Above

Model	Length	Retail
SNN142-	3	34.50
	10	39.50
	20	47.00
	25	51.50
	50	69.50
	100	107.50

12 Gauge

CBI SC-12 Power Series 12 Gauge - Round Flexible
Neutrik Speakon NL4FX Connectors
Built to Spec then Soldered for Maximum Durability

Options Same as Above

Model	Length	Retail
SNN122-	3	35.00
	10	41.50
	20	55.50
	25	62.00
	50	96.50
	100	155.00

10 Gauge

CBI SC-10 Power Series 10 Gauge - Super Heavy Duty
Neutrik Speakon NL4FX Connectors
Built to Spec then Soldered for Maximum Durability

The Ultimate Speakon Cable for MAX Power!

NL4FX - G&H "BOSS" MDP

Model	Length	Retail
SNN102-	6	41.00
	10	47.00
	25	69.00
	50	105.00
	100	175.00
SNNG*-		-2.00

4 Pole Wired 1+1-/ 2+2-

13 Gauge - 4 Pole

CBI MCS-134 Flexible Heavy Duty Wire
Neutrik Speakon NL4FX Connectors
Built to Spec then Soldered for Maximum Durability

Upgrade to 11 Gauge Max Power

Options:

1 FT Fan to 2 MDP Banana
1 FT Fan to 2 1/4" Male
1 FT Fan to 2 NL4FC ea 1+1-

Model	Length	Retail
SNN134-	6	50.50
	10	60.00
	20	80.00
	25	92.00
	50	142.50
SNN114-	100	246.50
SNNP*-		+10.00
SNNQ*-		+10.00
SNNNL4*-		+16.00

8 Pole Speakon Cables

13 Gauge Pro Sound

CBI MCS-138 Flexible Heavy Duty Wire
Neutrik Speakon NL8FC Connectors
Built to Spec then Soldered for Maximum Durability

Standard Cable for 8 Pole Speakon Applications

Options: Upgrade to MCS-128 12 Ga
4 x MDP or 4 x G&H 1/4", 6 ft Fan
4 x NL4FX (1+1-), 6 ft Fanout

Model	Length	Retail
SNN138-	6	96.50
	10	109.00
	20	141.00
	25	159.50
	30	172.50
	50	237.50
	100	400.00
SNN128- -P or -Q -Y4		+1.25/ft
		+50.00
		+60.00

SNEV - 11/4 + 13/4

CBI Special Design 11ga/13ga 8 Conductor
Neutrik Speakon NL8FC Connectors - Soldered for Durability
Heavy Duty Inner & Outer Jacketing Designed for Pro Sound
Design Gives Subs/Mid/Highs Exceptional Balance
While Maximizing Power vs. Cable Weight
in Array-type Speaker Applications

Manufactured for the World's Best Live Sound Events

Model	Length	Retail
SNEV-	6	116.50
	10	137.50
	20	190.00
	25	217.00
	30	244.00
	50	347.50
	100	612.50
	150	647.50
	200	847.50

Amphenol EP Cables

13 Gauge - 4, 6, or 8 Pole

Amphenol EP Series All Metal Connectors - Std. is Male to Female - Call
CBI MCS Series Multiconductor Speaker Wire - Any Length Available
Rugged Connector for Pro Sound Speakers and Panels

Model - Length	Retail
EP4-10	100.00
EP6-10	120.00
EP8-10	137.50

Speaker Snakes - 2-8 Channel

MTS Series Fan-Fan

Q = G&H 1/4", P = MDP, S = NL2FC 1+1-
Same Quality Construction as Our MT Series
CBI MCS 13ga (2-4ch) or LT 12ga (6-8ch)

Call for More Options or -CUSTOM Config

Box - Fan	Specify	Model - Length	Retail
1/4" - 1/4"	-QQ	MTS2 * -10	81.50
1/4" - MDP	-QP	MTS3 * -10	100.00
NL2 - NL2	-SS	MTS4 * -10	119.00
NL2 - MDP	-SP	MTS6 * -10	199.00
NL2 - 1/4"	-SQ		

PowerAudio

MTPA

Power & Audio in One Run!

(1) 14/3 Shielded Jacketed Group - Power
(2) 24ga Double Shielded Pairs - Audio
PowerCon, Edison, IEC, & XLR's

INTENDED FOR USE W/ POWERED SPEAKERS

Configuration	Model - Length	Retail
1 XLR, EDISON - IEC	MTPA-1X-E-IEC-25	135.00
1 XLR, EDISON - POWERCON	MTPA-1X-E-PC-25	135.00
1 XLR, EDISON - IEC	MTPA-1X-E-IEC-50	235.00
1 XLR, EDISON - POWERCON	MTPA-1X-E-PC-50	235.00

+ 12.50 for 2 XLR Configurations - Wire Also Rated for DATA

Professional 40-56ch Systems

1. Base System

14 ga Rolled Steel Box, Super-Durable Black Finish
 Choose 10u Rack Box or Stage Box with extended Base.
 Our finest technicians, hand-picked for their experience and skill, take pride in the quality of their work. Each StarPerformer is a work of art, inspected visually, and tested through an oscilloscope, as well as by ear with real audio signals.

Model	Total # Chan.	Std. Fan	100ft Base	Add. Length
SPR-	40	48"	-	-
SPS-	48	48"	-	-
	56	48"	-	-

Specify:

SPR-	Rack Mount or Stage Box
SPS-	Number of Returns, or All Inputs

2. Additional Splits

Monitor, Recording, Broadcast - Hardwired Passive splits
 Include 25ft Overall Base Length, Standard Fanout, Wiring into Box
 Strain Relief at Box, Metal Mesh Wire Hanger at Fan Whip
 Always Specify Wire Exit Location from Box

Total # Chan.	Std. Fan	25ft Base	Add. Length
32	36"	-	-
40	48"	-	-
48	48"	-	-
56	48"	-	-

3. Ground Lift Switches

Standard Rocker Switch Allows Flexibility in Solving Grounding Issues
 Highly Recommended for All Splitter Snakes - Standard SP Models Listed
 For Custom Applications, we use a Low Profile Toggle Switch

Option	Model	Add
-GL	SP40	-
	SP48	-
	SP56	-
-TGL		-

4. Isolation Transformers

Isolates Splits from Main Input Signal.
 Crucial for Maintaining a Clean Signal to Monitor / Recording Consoles
 Standard Transformer is Neutrik NTE-1 - Excellent for Live Audio Events

Other Upgrades Available: Studio Neutrik NTM-1 Iso
 Jensen Transformers

Option	# Ch.	Add
-T	32	-
	40	-
	48	-
	56	-
-TM		-
-TJ		-

5. Multipin Disconnects

MultiPin Model	Number of Channels										
	6	8	12	16	20	24	28	32	40	48	56*
PA19	X										
M39	X	X	X								
M61			X	X	X						
M85					X	X	X				
M122						X	X	X	X		
M150								X	X	X	
V159/VR								X	X	X	X
M176								X	X	X	X

***Veam is 53ch Max**

Includes BOTH Sides Completely Wired, Protective Caps Chassis or Inline

Other Disconnect Options are Available - Call for a Quote to Meet your Needs

ALWAYS CONFIRM PINOUT! - We use industry standards wherever possible, however variations may exist. If mating with pre-existing equipment, we need to ensure that your new CBI system will be 100% compatible.

More Options - Always Confirm Pricing and Availability

6. Fanout Options

- Extra Fanout Beyond 4ft, Double Heat Shrink at Stress pts -**XF**
- "Rock Series" Nylon Mesh Overbraid - Standard Black -**SSB**
- Rugged, Tangle-Free, Great Looking Vibrant Colors -**SSC**

7. Connector Options

- Neutrik Black XLRs - Box or Fanout -**BAG**
- Neutrik Black and Gold XLRs - Box or Fanout -**GOLD**
- Switchcraft Standard "A" Series XLRs on Fan -**SC**

8. Sub Snakes

6, 8, 12, or 16 Channel Drop Snakes for Accessing Specific Areas of the Stage
Adds Great Flexibility to your System - Basic Models, Use MC Series Page 25
Quick Disconnects Allow Direct Linkup to Main Box Head as well as Fast Setup

9. Additional Protection

- Custom Built Road Case to Store Your Complete System** -**CASE**
Durable, Std Truck Pack, Casters, The Perfect Case for Your Snake
- Metal Weave Mesh Strain Relief for Multipins** -**MESH**
Increased Durability against Pulling Tension on Longer Trunks
Available as Option to Replace Compression Style on All Sizes
- Pig Bags to Protect and Store Your Fanout Whips**

Complete Live Sound Systems - Ready to Ship!*

Most Popular Configurations - *Usually In Stock, Tested, Ready to Go - Call to Confirm

All Stock Systems are 10u Rack Mount with 200ft Mains and 50ft Monitor Splits

Both trunks have Multipin Disconnects at Box, Main has Disconnect at Fan

Belden Wire, Neutrik Connectors, 8 XLR Returns, Ground Lift Switches, Transformers

Disconnect Choices are M150, M176, and V159. 4 Piece System Shown Below:

Model
SPR48/40-200/50 GLT3M150
SPR48/40-200/50 GLT3M176
SPR56/48-200/50 GLT3M176
SPR48/40-200/50 GLT3Veam

Professional Multitrack

MT Series Fan-Fan Snakes

CBI / Belden Individually Shielded Multipair Wire - Black Flexible Jkt
Heat Shrink Tubing - Double Layers at Connector and Junction
Contrasting Numbers covered with Clear Heat Shrink on Fanout

Balanced: Neutrik Nickel 1/4" TRS - TRS
Neutrik TRS - NC3FX Fem XLR
Neutrik TRS - NC3MX Male XLR
NC3FX Fem XLR - NC3MX Male XLR

Unbalanced: Neutrik Nickel 1/4" TS - TS
Neutrik Nickel 1/4" TS - RCA Male
Neutrik Nickel RCA Male - RCA Male

Custom: Any Configuration - Signoff & Deposit Reqd.
Call Factory for a Prompt Quote
Basic Paired Cable Special MT2RR-10

Options: Gold Plated Version of Connector, Per each Connector
Prepped for Install, Fanout without Connectors
Always TT Studio Patching TRS Connector in place of 1/4" TRS
Confirm Price. Black "Rock Series" Mesh Covering on Fanouts
Deposit and/or Colored "Rock Series" Mesh Covering on Fanouts
Signoff Req. Neutrik NP2X Professional Compression 1/4" Mono
Neutrik NP3X Professional Compression 1/4" TRS
Colored Neutrik BSX Boots for XLRs - 8 Colors Avail

Specify Model	# Chan - Base Length	Std. Fan	Cost	Addl. Length
	MT2* - 10	4"	-	-
	MT4* - 10	6"	-	-
	MT6* - 10	8"	-	-
-BLA	MT8* - 10	12"	-	-
-BLB	MT9* - 10	12"	-	-
-BLC	MT10* - 10	12"	-	-
-XX	MT12* - 10	18"	-	-
	MT16* - 10	24"	-	-
-QQ	MT20* - 10	24"	-	-
-RQ	MT24* - 10	24"	-	-
-RR	MT28* - 10	36"	-	-
	MT32* - 10	36"	-	-
-CUST	MT40* - 10	48"	-	-
	MT48* - 10	48"	-	-
	MT56* - 10	48"	-	-

-GOLD
-PREP
-TT
-SSB
-SSC
-NP2X
-NP3X
-BSX

Addl. Fan Length
per Ft per Ch. per Side

1. # Channels 2. Connectors 3. Overall Length 4. Confirm Fanouts 5. Options? 6. Std. Labelling & Color Code?

IS Series Insert Snakes

Same Construction and Components as MT Series - See Options Above
Separate Shielded Pairs used for Send and Receive

When Ordering IS1 as a long Y from page 9, use the Corresponding 3 Numbers

All 1/4": Neutrik Nickel 1/4" TRS Split to
1/4" Sends (Tip) and 1/4" Returns (Ring)

XLR: Neutrik Nickel 1/4" TRS Split to
XLR Male Sends (Tip) and XLR Fem Ret. (Ring)

Specify Model	# Chan - Base Length	Std. Fan	Cost	Addl. Length
	IS1* - 10	4"	-	-
	IS2* - 10	6"	-	-
-###	IS4* - 10	12"	-	-
	IS6* - 10	18"	-	-
-Q	IS8* - 10	24"	-	-
	IS12* - 10	24"	-	-
	IS16* - 10	36"	-	-
-X	IS20* - 10	48"	-	-
	IS24* - 10	48"	-	-
	IS28* - 10	48"	-	-

MC Performer Series Snakes

A Series Pro Snakes

CBI / Belden Individually Shielded Multipair Wire - Black Flexible Jkt
 Heat Shrink Tubing - Double Layers at Connector and Junction
 Contrasting Numbers covered with Clear Heat Shrink on Fanout
 Stage Box is 14/16 Ga Rolled Steel, Durable Finish, Silk-screened
 Neutrik NC3FDL Locking XLR's in Box - NJ3FP6C Series Locking TRS 1/4"
 Neutrik X-Series XLR's / Neutrik 1/4" on Fan - Metal Mesh Wire Hanger

Specify: Inputs / Returns adding up to Total Channels
 Config. of Returns: XLR or 1/4" TRS
Model # Example: MCA20-1604Q-100

Options: Same as MT Series (opposite page)

Custom: Any Configuration - Signoff & Deposit Reqd.
 Monitor Splits - Built to Your Specs

Specify Config	Total # Chan.	Std. Fan	50ft	100ft	Add. Length
MCA-	6	8"	-	-	-
	8	12"	-	-	-
	9	12"	-	-	-
	12	18"	-	-	-
	16	24"	-	-	-
-(IN)(RT) -X or -Q	20	24"	-	-	-
	24	24"	-	-	-
	28	24"	-	-	-
	32	36"	-	-	-
	40	48"	-	-	-

-CUST MS- Call us Today for a Prompt Quote on Splitter Snakes or Any Custom Needs

1. # Channels 2. # Ret.. X or Q? 3. Overall Length 4. Confirm Fanouts 5. Options? 6. Std. Label & Color Code?

B Series Standard Snakes

CBI / Belden Individually Shielded Multipair Wire - Black Flexible Jkt
 Heat Shrink Tubing - Double Layers at Connector and Junction
 Contrasting Numbers covered with Clear Heat Shrink on Fanout
 Stage Box is 14/16 Ga Rolled Steel, Durable Finish, Silk-screened, with Strain Relief
 CBI Snakes Feature Top Quality Components and the Finest Craftsmanship!
 Neutrik NC3FPP Non-Locking XLR's in Box
 Neutrik Non-locking TRS 1/4" Panel Mt
 CBI C-XLR Nickel Connectors on Fan

Specify: Inputs / Returns adding up to Total Channels
 Config. of Returns: XLR or 1/4" TRS

Specify Model	Total # Chan.	Std. Fan	50ft	100ft	Add. Length
MCB-	6	8"	-	-	-
	8	12"	-	-	-
	9	12"	-	-	-
	12	18"	-	-	-
	16	24"	-	-	-
	20	24"	-	-	-
	24	24"	-	-	-
	28	24"	-	-	-
-(IN)(RT) -X or -Q	32	36"	-	-	-
	40	48"	-	-	-

APS Series "Power" Snakes

Designed for Powered Mixers - Components same as MCB Series
 Enclosed Speaker Lines - 14 Gauge to Jumbo 1/4" on Fan
 Parallel 1/4" Left & Right Speaker Outputs in Box
 2 TRS 1/4" Audio Returns, Standard Models Listed

Model - Length	Std. Fan	Inputs/ Ret/Spkr	Cost	Add. Length
APS0822-50	12"	8/2/2	-	-
APS1222-100	18"	12/2/2	-	-
APS1622-100	24"	16/2/2	-	-
APS1624-100	24"	16/2/4	-	-

Analog Cables

D-sub 25 Pin

CBI / Belden Studio Quality Wire - 100% Shielded
AMP Solid Metal 25 Pin D-Sub Male with Gold Pins
8 Channels - Neutrik Nickel 1/4" Male TRS

Options: 8 Neutrik NC3M(F)X Male(Fem) XLRs
8 Studio TT Tiny Telephone Patching
Male 25 Pin - Male 25 Pin
Neutrik NP3X Compression TRS 1/4"

Model	Length	Retail
DS-	6	108.00
	10	114.50
	15	123.50
	20	132.00
DSM(F)X-		+25.00
DSTT-		+80.00
DSP-		same
DSNPX-		+50.00

Mogami 25 Pin

Mogami 2932 Analog Studio 8pr - Super Flexible
AMP Solid Metal 25 Pin D-Sub Male with Gold Pins
G&H 100% Gold Plated OFC Solid Shaft TRS 1/4"

Options: 8 Neutrik GOLD Male XLRs
8 Neutrik GOLD Female XLRs
Male 25 Pin - Male 25 Pin
Neutrik NP3X Compression TRS

Model	Length	Retail
DSM-	6	196.50
	10	224.00
	15	260.00
	20	296.50
DSMXM-		same
DSFXM-		same
DSPM-		same
DSNPXM-		same

ADAT - 56 Pin

Edac 56 Male w/ Actuating Screw - All Metal Housing with Gold Contacts
Belden / CBI Performer Series Flexible Multipair - Neutrik TRS 1/4" & XLRs
Wired for Alesis ADAT machines - Spec. 16 TRS, 8 M&F XLRs, or Pin-Pin

Model - Length	Retail
A88TRS-10	258.00
A88MFX-10	290.00
A88PP-10	278.00
Additional Length	'+2.50 /ft

Digital Cables

D-sub 25 Pin AES

Belden 9732 Digital 8 Pair - 100% Shielded, Gray
AMP Solid Metal 25 Pin D-Sub Male with Gold Pins
8 Channels In/Out - Neutrik GOLD XLRs, 4M/4F

Options: **Mogami 3162 Digital 8pr**
Pin - Pin, Tascam-Tascam Pin out
"T" = **Tascam** Pin - Pin, Yamaha-Tascam Pin out
"Y" = **Yamaha** Pin - Pin, Yamaha-Yamaha Pin out

Model	Length	Retail	
DSAES-T-	6	157.00	
	DSAES-Y-	10	166.50
		15	184.00
		20	200.00
DSMAES-(T/Y)		+6.00 /ft	
DSPAES-TT-		same	
DSPAES-YT-		same	
DSPAES-YY-		same	

AES/EBU Cable

Belden 1696A AES/EBU 110ohm Wire - Dbl Shielding, Flexible, Top Quality
Neutrik Gold X Series 100% Strain Relief XLR Connectors

Model	Length	Retail
AES/EBU-	6	31.00
	10	34.00
	20	47.50

S/PDIF

Belden or Carol RG59 75ohm Coax with Braided Shield
Gold Plated RCA Connectors for Superior Connection

Model	Length	Retail
SPDIF-	6	16.00
	10	19.00
	20	25.00

Synch - 9 Pin

9 Pin D-sub Male-Male Synchronization Cable, Belden Wire, All metal D-sub

Model	Length	Retail
SYNCH-	6	32.50
	12	40.00

Patch Bays

Neutrik, Switchcraft, and Rean Patchbays - 1/4" TRS & TT
 Popular Models Listed - Many Available - Call for Pricing & Delivery

Model	Retail
NYS-SPP-L	222.50
NPPA-TT-S	1487.50
MA96-10	1122.50
S-TTP96AS-SNN	937.50
S-MT48FN	675.00

Custom Wired TT Patchbays

Built to Order, Ready to Install -You plan it, we'll make it.

Specify Full, Half, or Non Normaling, Channel by Channel.

Each grouping of Channels can be Any Length

Mogami Wire D-Sub Termination
 Gold Connectors EDAC / ELCO Termination

TT / TB Patch Cables

Pro Studio Patching

TT - Belden 9397 22ga Patented French Braided Studio Wire - Ultra Flexible

Neutrik / G&H Bantam TRS Connectors - Professional Quality Patching

Options: Neutrik NP3TB Military Tip TRS - Belden MLU Ultimate
 TT to Male (or Female) XLR
 Neutrik Premade Molded TT Cables

Model	Length	Retail
TT-	1	29.95
	18IN	30.95
	2	31.50
TB-	3	32.50
	6	35.95
-M(F)X		
NTT-		

Press Boxes

Durable Isolated Output Boxes for Providing Multiple, Independent Signals from a Single Mic Source with a Direct Passthrough. Each Output Transformer Isolated
 All Neutrik Connectors and Components, Belden Wire, Durable 14/16ga Steel box

Options: Ground Lift Toggle Switches, ea.
 Upgrade Studio Transformer NTM-1

Model	Chan	Retail
PBX-	6	300.00
	12	590.00
	16	720.00
	24	990.00
-GL		+12.00ea
-NTM		+60.00ea

Splitter Boxes

Transformer Isolated Splitter Boxes - 14/16 Ga Steel - Black Enamel

Each Channel Splits One XLR Input to Direct and Iso XLR Outputs

All Neutrik Connectors and Components, Belden Wire, Durable 14/16ga Steel box

Options: Std 19" Rack Panel Versions
 Upgrade Studio Transformer NTM-1
 Jensen Transformer

Model	In-Out	Retail
SBX-	4-8	350.00
	8-16	600.00
	(2x Iso) 8-24	900.00
	16-32	1200.00
	24-48	1750.00
-RACK		Call
-NTM		+60.00ea
-JTM		+90.00ea

Single Coax

RG59 - 75ohm

Crimped & Soldered BNC / F / RCA Males w/ Shrink
For Standard Single Line Analog Video Apps

RG59 75ohm Video Cable

RG59 75ohm Stranded Video

RCA M-M RG59 Stranded

RG59 75ohm Video Cable

Call for Plenum Rated Installation Versions

RG58 50ohm BNC Data Cable

Specify Model	Length	Retail
	3	13.00
	6	14.50
	10	16.50
BNC59-	15	20.00
BNC59S-	20	23.50
RCA59S-	25	27.00
F59-	30	31.00
-PLENUM	50	45.00
BNC58-	100	74.00

RG6 - 75ohm Digital

Belden Professional Quality RG6 Wire - True 75ohm BNCs - Crimped and Soldered
75 ohm Digital Broadcast/Video Cables - Double Shielded Digital Cable / Sattelite
Pro Quality Video Cable for Any Application

Model	Length	Retail
RG6-	6	21.50
	25	32.50
	50	50.00
	100	74.00

S-Video

Composite 75ohm 4 Pin

Belden 1808A Dual RG59 Coax - Braided Shield
Gold Contact, Metal Barrel 4 Pin Mini-DIN - Male-Male, Soldered
Wired for Y/C Video - Perfect for Professional or Home Installs

A Superior Quality S-Video Cable

Model	Length	Retail
SVHS-	3	34.50
	6	39.00
	10	45.00
	15	52.00
	20	60.00
	50	106.50

Multi-Coax

VGA / Component

CBI / Belden High Quality Broadcast Wire - 5 x 75ohm

15 Pin HD All Metal D-sub, Male - Male

15 Pin HD All Metal D-sub Male - 5 BNC

5 x True 75 ohm BNC, Male to Male

5 x Gold Plated RCA, Male to Male

15 Pin HD Female Extension

Specify Model	Length	Retail
	3	122.00
	10	141.50
VGA-	25	197.50
VGA5B-	50	261.50
RGBHV-	100	462.50
-RR	150	660.00
-1F		

Professional RGB or A/V Combo

CBI / Belden High Quality Broadcast Wire - 3 x 75ohm - Red / Grn / Blu

3 x True 75 ohm BNC, Male to Male

3 x Gold Plated RCA, M to M

Pro A/V Color Code: 3 x Gold Plated RCA, M to M - Red/Blk/Yel

Specify Model	Length	Retail
	3	55.50
	10	76.25
RGB-	25	117.50
RGBRR-	50	192.50
RKYRR-	100	322.50

For a Variety of Video Adapters and Connectors see pages 32-33

INSTALL

RP - Custom 19" Rack Panels

Heavy Steel with Black Finish, 3" Deep Box for Total Enclosure, 1.75" per Space for Standard Racks
 Easy Patching for Numerous Applications - Saves Equipment Wear - Organizes & Simplifies Rack Wiring
 Fax Drawing for a Prompt Price Quote Today - Very Fast Build Time! *Box comes with 100% Strain Relief

Panel	Cost
RP1	-
RP2	-
RP3	-
RP4	-
RP5	-

Connector	Description	Each
NC3FD-L-1	Female XLR	-
NC3MD-L	Male XLR	-
NJ3FP6C	Fem 1/4 TRS Lock	-
S-12B	Fem 1/4 TRS	-
S-11	Fem 1/4 Mono	-
AC-DUPLEX	Duplex Power Outlet	-
NL4MP	4pl Speakon, Rect	-
NL4MPR	4pl Speakon, Round	-
NL8MPR	8pl Speakon, Round	-
C-3501	Fem RCA	-
MDPFP	Dual Banana	-
Any Other - See Bulk Connectors		-

Audio - 3' Tail	Each
Blunt	-
Neutrik XLR	-
1/4" Mono	-
NYS228 1/4" TRS	-
RCA	-

Box*	Cost
RB1	-
RB2	-
RB3	-
RB4	-
RB5	-

Speaker - 3' Tail	Each
Blunt	-
Pomona MDP	-
Spade Lug	-
Jumbo 1/4"	-
NL4FC / X	-

FB - Floor Pockets

Professional Installation & Stage Floor Pockets - Tapered Edge
 Heavy Steel Construction with Black Finish, Ready to Load
 2 Sizes: 4 or 8 Standard Neutrik "D" Panel Cutouts

OPTIONS:

- 4F/8F Pre-Loaded with Neutrik NC3FDL-1 Panel Mount XLRs
- EB Galvanized Electric Back Box with Knockouts

We Will Pre-Load and Wire to Meet your Needs - Call Us!

Model	Retail
FB4	149.00
FB8	209.00
FB4 - 4F	169.00
FB8 - 8F	229.00
FB4 - EB	35.00
FB8 - EB	49.00

SB - "Stud" Boxes

Heavy Duty Steel w/ Black Finish Hinged and Flanged Enclosed Boxes
 Designed to Install Between 16" Studs
 Inside Dimensions: S = 16 7/8" x 5 1/2" x 3", L = 16 7/8" x 10 11/16" x 3"

Model	Retail
SB-S	179.99
SB-L	239.99

RC - Cabinet Recess Plates

Heavy Steel with Black Finish, Rectangle for Cabinet Mounting
 Accommodates 2 Standard Connectors - See RP Pricing Above
 Inside Dimensions: -S 4 5/8" x 2 5/8" -L 5 5/8" x 3 5/8"

Model	Retail
RC-S	12.95
RC-L	14.95

WP - Standard Wall Plate

Model	Gang	Loaded With	Retail
WP1-1F (or 1M)	Single	1 Neutrik DL Series Female (or Male) XLR	11.50
WP1-2F (or 2M)	Single	2 Neutrik DL Series Female (or Male) XLRs	17.50
WP2-3F (or 3M)	Double	3 Neutrik DL Series Female (or Male) XLRs	25.00
WP2-4F (or 4M)	Double	4 Neutrik DL Series Female (or Male) XLRs	30.00
WP1-1C11 (or 1C12B)	Single	1 C-12B TRS (or C-11 TS) Female 1/4"	8.50
WP1-2C11 (or 2C12B)	Single	2 C-12B TRS (or C-11 TS) Female 1/4"	10.50
WP1-1L	Single	1 Neutrik TRS Fem. 1/4" Locking	15.50
WP1-2L	Single	2 Neutrik TRS Fem. 1/4" Locking	25.00
WP2-3L	Double	3 Neutrik TRS Fem. 1/4" Locking	40.00
WP2-4L	Double	4 Neutrik TRS Fem. 1/4" Locking	50.00
WP1-1NL4	Single	1 Neutrik Speakon 4 Pole NL4MP	13.00
WP1-2NL4	Single	2 Neutrik Speakon 4 Pole NL4MP	21.00
WP1-1VGAPT	Single	1 15pinHD Fem-Fem Passthrough	25.00
WP1-1NE8	Single	1 Ethercon CAT5E Panel Mt	25.00

MBX - Audio Stage Boxes *Performer Series*

- U 14ga Back / 16ga Front, Textured Black Enamel Finish, Silk-screen Numbering, Unloaded
- A A-Series - Neutrik DL-Series Locking XLR's, Neutrik Locking 1/4", Box Strain Relief
- B B-Series - Neutrik P-Series Non-Locking XLR's, Neutrik Non-Locking 1/4", Box Strain Relief

Model	L x W	Hole	Standard Configuration	Unloaded	A-Series	B-Series
MCBX 6 - *	9.5" x 5.75"	1/2"	All Inputs, # 1-6	-	-	-
MCBX 8 - *	9.5" x 5.75"	1/2"	All Inputs, # 1-8	-	-	-
MCBX 9 - *	9.5" x 5.75"	1/2"	6 Inputs # 1-6, 3 Returns # 7-9	-	-	-
MCBX 12 - *	9.5" x 7.12"	3/4"	8 Inputs # 1-8, 4 Returns # 9-12	-	-	-
MCBX 16 - *	11.5" x 7.12"	3/4"	12 Inputs # 1-12, 4 Returns # 13-16	-	-	-
MCBX 20 - *	13.5" x 7.12"	3/4"	16 Inputs # 1-16, 4 Returns # 17-20	-	-	-
MCBX 24 - *	15.5" x 7.12"	1"	20 Inputs # 1-20, 4 Returns # 21-24	-	-	-
MCBX 28 - *	17.5" x 7.12"	1"	24 Inputs # 1-24, 4 Returns # 25-28	-	-	-
MCBX 32 - *	19.5" x 7.12"	1"	24 Inputs # 1-24, 8 Returns # 25-32	-	-	-
MCBX 40 - *	21.5" x 7.12"	1"	32 Inputs # 1-32, 8 Returns # 33-40	-	-	-
SPBX 40 - *	17.5" x 17"	1"	32 Inputs # 1-32, 8 Returns # 33-40	-	-	-
SPBX 48 - *	17.5" x 17"	1"	40 Inputs # 1-40, 8 Returns # 41-48	-	-	-
SPBX 56 - *	17.5" x 17"	1"	48 Inputs # 1-48, 8 Returns # 49-56	-	-	-
PROJECT	8.25" x 5.2"	1/2"	Blank, or * Punched / Loaded to Order	-	*	*

Specify 1/4" or XLR Returns - Call for Pricing on Disconnects or Custom Configurations

Bulk Accessory Items

Model #	Description	Retail
CTV-BULK	Cable Ties, Velcro 8", 100 pcs Bulk, Mix & Match - Red, Blue, Blk, or Gry	100.00
SR-S	Box Strain Relief, Small, Wire Mesh, 1/2" dia Hole, 6-9 Pair Wire	19.00
SR-M	Box Strain Relief, Medium, Wire Mesh, 3/4" dia Hole, 12-20 Pair Wire	21.00
SR-L	Box Strain Relief, Large, Wire Mesh, 1" dia Hole, 24-56 Pair Wire	24.00
SRN-S	Box Strain Relief, Small, Nylon 100% Compression, 1/2" dia Hole, 6-9 Pair Wire	8.00
SRN-M	Box Strain Relief, Med., Nylon 100% Compression, 3/4" dia Hole, 12-20 Pair Wire	10.00
ST-1/8	Heat Shrink Tubing, 1/8" Diameter, Black, Clear	0.50
ST-3/16	Heat Shrink Tubing, 3/16" Diameter, Black, Clear	0.60
ST-1/4	Heat Shrink Tubing, 1/4" Diameter, Black + 8 Colors	0.75
ST-3/8	Heat Shrink Tubing, 3/8" Diameter, Black + 8 Colors	1.00
ST-1/2	Heat Shrink Tubing, 1/2" Diameter, Black + 8 Colors	1.20
ST-3/4	Heat Shrink Tubing, 3/4" Diameter, Black, Clear	1.50
ST-1	Heat Shrink Tubing, 1" Diameter, Black	2.00
ST-1.5	Heat Shrink Tubing, 1 1/2" Diameter, Black	3.00
TS-12	Terminal Strip, Double, 12 Point	7.95
WH-S	Wire Hanger Strain Relief, Small, Wire Mesh, 6-9 Pair Wire	17.00
WH-M	Wire Hanger Strain Relief, Medium, Wire Mesh, 12-28 Pair Wire	19.00
WH-L	Wire Hanger Strain Relief, Large, Wire Mesh, 32-56 Pair Wire	21.00
PDB-24	Punchdown Block 24 Channel Parallel, Wall or Panel Mount	220.00

AN Series - XLR

The AN Series Adapters are Shielded and Sealed.

Each Adapter is Shipped Completely Wired to Standard Specifications.

* Pin 2 Hot

Special Wiring Available Upon Request

Neutrik Adapters Available Call for Pricing

Description		Model	Retail
Male XLR	Fem XLR in Phase	AN 420	18.00
Male XLR	Fem XLR Ground Lifted	AN 420 GL	18.00
Male XLR	Fem XLR Phase Reverse	AN 420 PR	18.00
Male XLR	Male XLR in Phase	AN 421	18.00
Female XLR	Female XLR in Phase	AN 422	18.00
Male XLR	Male TRS 1/4"	AN 423*	19.00
Female XLR	Male TRS 1/4"	AN 424*	19.00
Male XLR	Fem TRS 1/4"	AN 425*	20.00
Female XLR	Fem TRS 1/4"	AN 426*	20.00
Male XLR	RCA Male	AN 427	19.00
Female XLR	RCA Male	AN 428	19.00
Male XLR	RCA Female	AN 429	19.00
Female XLR	RCA Female	AN 430	19.00
Male XLR	Male Mono 1/4"	AN 431	19.00
Female XLR	Male Mono 1/4"	AN 432	24.00

C Series - Audio

Description		Model	Retail
1/8" TRS Male	1/4" TRS Female	C-103	2.50
1/4" TRS Male	1/8" TRS Female	C-104	2.50
RCA Male Y-Adapter	(2) RCA Female	C-330F	2.50
RCA Male, Solid Body T	(2) RCA Female, Gold Plated	C-330F-PRO	10.00
1/4" Mono Male, Y-Adapter	(2) RCA Female	C-330PJ	2.50
RCA Male	1/4" Female Mono	C-336	3.00
1/4" Mono Male, Y-Adapter	(2) 1/4" Mono Female	C-340	2.50
1/4" Mono Male	RCA Female	C-345	2.50
RCA Female, Coupler	RCA Female	C-349	3.00
1/4" Mono Female, Coupler	1/4" Female Mono	C-361	4.50
1/4" Mono Male	1/4" Mono Male	C-363	4.50
1/8" Mono Male	RCA Female	C-370	2.50
1/8" Mono Male	1/4" Female Mono	C-374	2.50

VA Series - Video

Description		Model	Retail
BNC Male	"F" Female	VA17	4.50
"F" Female	"F" Female, Coupler	VA87	3.00
RCA Male	"F" Female	VA07	3.00
BNC Female, T-Adapter	(2) BNC Female	VA19	5.00
BNC Male, T-Adapter	(2) BNC Female	VA35	5.00
"F" Male	BNC Female	VA37	4.50
BNC Female, Coupler	BNC Female	VA16	4.50
RCA Male	BNC Female	VA01	3.00
"F" Male	RCA Female	VA22	4.00
BNC Male	RCA Female	VA18	4.50

Any Adapter Available Pre-Packaged for Retail Display - "CB2" Series Blister Pack

C Series - Audio

High Quality, Low Cost
Alternatives to Brand Name
Connectors

Available in Bubble-Pack
For Easy Retail Display
Add CB2- in Front of Model

Description	Model	Retail
1/4" Mono Female Standard Chassis	C-11	2.00
1/4" Mono Female Long Chassis	C-11L	2.50
1/4" Mono Female Cable Mount	C-121	5.00
1/8" Mono Female Cable Mount	C-125	2.50
1/4" Mono Female Cable Mount, Jumbo	C-128	5.00
1/4" TRS Female Chassis	C-12B	2.50
Jumbo 1/4" Mono Male	C-184	4.00
Right Angle 1/4" Mono Male Barrel-Style	C-226	4.00
Right Angle 1/4" Male Barrel-Style, 100% Gold-Plated	C-226G	5.00
Right Angle 1/4" Mono Male, Flat Style	C-228	2.50
Right Angle 1/4" TRS Male, Flat Style	C-238	4.00
1/4" Mono Male Cable Mount, Nickel Plated	C-280	2.25
1/4" Mono Male Gold Plated	C-280G	3.00
RCA Female Panel Mount	C-3501	2.50
RCA Male Cable Mount, Gold Plated	C-3502G	4.00
Right Angle RCA Male Cable Mt	C-3502R	4.00
RCA Female Cable Mount	C-3503	3.00
1/8" Mono Male Cable Mount	C-770	2.50
XLR Female 3 Pin Panel Mount	C-D3F	3.25
XLR Male 3 Pin Panel Mount	C-D3M	2.00
DIN Female 5 Pin Panel Mount	C-FM5D	2.50
Banana Plug, Standard Dual Cable Mount	C-MDP	2.50
Banana Female, Standard Dual Panel Mount	C-MDPFBP	5.00
1/8" TRS Female Cable Mount	C-WFP	2.50
1/8" TRS Male Cable Mount	C-WMP	2.50
XLR Female Cable Mount, SC Style, Nickel	C-XLRF-SC	3.00
XLR Male Cable Mount, SC Style, Nickel	C-XLRM-SC	2.50
XLR Female Cable Mount, N Style, Nickel	C-XLRF-N	3.00
XLR Male Cable Mount, N Style, Nickel	C-XLRM-N	2.50
XLR Female Cable Mount, N Style, Black	C-XLRF-NB	3.00
XLR Male Cable Mount, N Style, Black	C-XLRM-NB	2.50

Video

Description	Model	Retail
"F" Male Cable Mount Crimp RG59	VC01	1.79
BNC Male Cable Mount Crimp RG6 - for Belden 9248	BNC9248	3.75
BNC Male Cable Mount Crimp RG58 - for Belden 8240	BNC8240	3.00
BNC Male Cable Mount Crimp RG59 - for Belden 8241	BNC8241	3.00
BNC Mini Male Cable Mt Crimp RG59 - for Belden 14xx	BNC1417	5.50
BNC Female Panel Mount, Isolated	VC28	4.50
S-VHS 4 Pin DIN Connector, Plastic	VCSVP	4.00
S-VHS 4 Pin DIN Connector, All Metal w/ Gold	VCSVG	7.50
Neutrik Pro Push-On BNC's	NBNC	7.50
VGA 15 Pin HD D-Sub Male Cable Mt with Metal Hood	DB15HDM	18.00
VGA 15 Pin HD D-Sub Female Cable Mt with Metal Hood	DB15HDF	18.00
VGA 15 Pin Female Panel Mount	DB15HD-PF	4.50

Retail Accessories

Description	Model	Retail
Blister Packed Cable Ties, Velcro 8", 4 Pack, Assorted Colors	CB2-CTV8	4.99
Mic Clip with Brass Insert, Black Finish, Bulk, Slip-on, Plastic	MIC-S	2.50
Power Supply Cord, 16ga, 6ft, Std 3 Prong, Black	PSC16-6	9.00
Wind Screens, Black, Fits Ball-type Mic, 4 Pack, Black	WSB	9.95
Wind Screens, Black, Fits Ball-type Mic, 4 Pack, Colors	WSC	9.95
CBI Gig Bag - Black Duffle Bag with Logo	GIGBAG	14.99
CBI T-Shirt, Black with Logo, Size Large	TS-L	10.99

XLR Cable Connectors

Pin	Model	Description	Retail
3 PIN	NC3FX-1	Female XLR, Nickel, Hard Boot	5.12
	NC3FX	Female XLR, Nickel, Soft Boot	5.44
	NC3FX-BAG	Female XLR, Black, Soft Boot	6.76
	NC3FX-B	Female XLR, Black with Gold Contacts	8.40
	NC3FX-S	Female XLR, w/ Rotary on/off Switch, Nickel	17.96
	NC3FRC	Female XLR, Right Angle, Nickel	15.52
	NC3MX-1	Male XLR, Nickel, Hard Boot	4.64
	NC3MX	Male XLR, Nickel, Soft Boot	4.88
	NC3MX-BAG	Male XLR, Black, Soft Boot	6.32
	NC3MX-B	Male XLR, Black with Gold Contacts	7.52
NC3MRC	Male XLR, Right Angle, Nickel	14.84	
4 Pin	NC4FX	Female XLR, Nickel	9.28
	NC4FX-BAG	Female XLR, Black	10.72
	NC4FX-B	Female XLR, Black with Gold Contacts	12.40
	NC4MX	Male XLR, Nickel	6.88
	NC4MX-BAG	Male XLR, Black	8.08
	NC4MX-B	Male XLR, Black with Gold Contacts	9.48
5 Pin	NC5FX	Female XLR, Nickel	11.40
	NC5FX-BAG	Female XLR, Black	12.88
	NC5MX	Male XLR, Nickel	8.72
	NC5MX-BAG	Male XLR, Black	9.76
6 & 7 Pin	NC6FX	Female XLR, Nickel	13.88
	NC6FXS	Female XLR, Nickel Switchcraft Style	13.88
	NC6MX	Male XLR, Nickel	9.24
	NC6MXS	Male XLR, Nickel Switchcraft Style	9.24
	NC7FX	Female XLR, Nickel	16.00
	NC7MX	Male XLR, Nickel	11.56
color coded	BSX-[Color]	XLR Boots, -WT-GR-V-BL-GN-Y-O-R-BR-BLK	1.23
	XCR-[Color]	XLR-Rings, -WT-GR-V-BL-GN-Y-O-R-BR-BLK	0.73
3 Pin	NC3FDL-L-1	Female XLR, Locking, Nickel	5.56
	NC3FDL-L-1-BAG	Female XLR, Locking, Black	6.72
	NC3FDL-L-1-B	Female XLR, Locking, Black with Gold Contacts	8.53
	NC3FP-1	Female XLR, Locking, Nickel, Rectangle	5.84
	NC3FPP	Female XLR, Black Plastic, Non-Locking	2.88
	NC3MD-L-1	Male XLR, Nickel	5.32
	NC3MD-L-1-BAG	Male XLR, Black	7.48
	NC3MD-L-1-B	Male XLR, Black with Gold Contacts	8.50
	NC3MP	Male XLR, Locking, Nickel, Rectangle	5.80
	NC3MPP	Male XLR, Black Plastic	2.84
4 & 5 Pin	NC4FD-L-1	Female XLR, Locking, Nickel	11.12
	NC4MD-L-1	Male XLR, Nickel	7.28
	NC5FD-L-1	Female XLR, Locking, Nickel	15.04
	NC5MD-L-1	Male XLR, Nickel	11.76
6 & 7 Pin	NC6FD-L-1	Female XLR, Locking, Nickel	22.12
	NC6MD-L-1	Male XLR, Nickel	14.92
	NC7FD-L-1	Female XLR, Locking, Nickel	26.04
Combo	NCJ6FI-S	COMBO Female XLR / Female TRS 1/4", Locking	8.13
1/4" Panel Mount	NJ3FP6C	Female Locking TRS 1/4", Nickel	10.48
	NJ3FP6C-P	Female Locking TRS 1/4", Plastic	10.24
	NJ3FP6C-BAG	Female Locking TRS 1/4", Black	11.24
	NYS216	Female TRS 1/4" Black Plastic, Iso Ground	1.73
	NYS220	Female TS 1/4" Thick Panel	4.38
	NYS220/3	Female TRS 1/4" Thick Panel	4.38
	NYS221	Female TS 1/4" Thick Panel, with Strap Ring	4.38
	NYS229 (or -L)	Female TS 1/4" Panel, Std or .375" Bushing	2.48
NYS230	Female TRS 1/4" Panel, Standard	2.48	
Misc.	DBA	D-Series Flat Hole Plug, Black Plastic	1.40
	DSS-(Color)	ID Plate, -WT-GR-V-BL-GN-Y-O-R-BR-BLK	1.73
	SCDF (or SCDM)	Rubber Cover, Female "D" (or Male "D", "NL*MP")	1.73

XLR Panel Connectors

Cable Connectors

Model	Description	Retail
NP2X	Plug 1/4" mono C+ series - nickel/silver	5.76
NP2C (-BAG)	Male 1/4", Compression Style, Nickel (Black)	6.28
NP2C-T10AA	Male 1/4", Built in Transformer, Nickel	43.52
NP2C-SILENT	Male 1/4", Silent Gold Ground Lift	17.32
NP2RCS	Plug 1/4" mono - slim right angle - black plastic/silver	6.60
NP3X	Plug 1/4" stereo C+ series - nickel/silver	8.60
NP3C	Male TRS 1/4", Compression Style, Nickel	9.04
NJ3FC6	Female Locking TRS 1/4", Nickel, Cable Mount	12.36
NJ3FC6-BAG	Female Locking TRS 1/4", Black, Cable Mount	12.96
NYS224	Male 1/4", Nickel	2.48
NYS224L	Male 1/4", Nickel, Large Hole, 8mm OD	2.60
NYS228	Male TRS 1/4" , Nickel	3.73
NP3TT-B (R)	Male TRS 1/4" TT Bantam, Black or Red	10.75
NP3TB-B (R)	Male TRS 1/4" Military Tip, Black or Red	12.60
NYS231	Male TRS 3.5mm (1/8") Mini Cable Mt, Nickel	2.48
NTP3RC	Plug 3.5mm right angle - black plastic/nickel	6.44
NYS322	Male 5 Pin Din w/Clamp, Metal Housing	3.13
NYS323	Male 7 Pin Din w/Clamp, Metal Housing	4.88
NYS352	Male RCA, Nickel, Rubber Boot	2.88
NF2D-Color	Jacks RCA D series - blk, blue, gr, red, ylw - nickel	7.20
NF2CB/2	Profi Gold Professional RCA's, Pair	32.96

Speakon

Model	Description	Retail
NL2FC	2 Pole Female Cable Mount	5.80
NL4FC	4 Pole Female Cable Mount	9.80
NL4FX	4 Pole Female Cable Mount	9.60
NL4FRX	4 Pole Female Cable Mount, Right Angle	12.48
NLT4FX	4 Pole Female Cable Mount STX	18.72
NLT4MX	4 Pole Male Cable Mount STX	18.24
NL8FC	8 Pole Female Cable Mount	21.44
NL2MP	2 Pole Square Flange Male Panel	4.63
NL4MP	4 Pole Square Flange Male Panel	5.90
NL4MPR	4 Pole Round Flange Male Panel	6.40
NL8MPR	8 Pole Round Flange Male Panel, Nickel	14.40
NA4LJ	Adapter - Speakon NL4FC to Female 1/4"	14.38
NL4MMX	4 Pole Male to Male Coupler, Double Locking	12.73
NL8MM	8 Pole Male to Male Coupler	37.04
LRX	Conversion Kit, NL4FX to Right Angle	3.73

Powercon AC

Model	Description	Retail
NAC3FCA	Cable End, Power In, Blue	12.32
NAC3FCB	Cable End, Power Out, Gray	12.32
NAC3MPA	Receptacle, Power In, Blue	6.20
NAC3MPB	Receptacle, Power Out, Gray	6.20
NAC3MM	Coupler, Mates with FCA & FCB	30.32

Data/Video

Model	Description	Retail
NE8MC	Cable Housing, Nickel (RJ-45 plug not incl.)	5.32
NE8FDV-YK	"D" Style receptacle, IDC Krone Terminals	16.44
NE8FDV-Y110	"D" Style receptacle, IDC 110 Punchdown	16.44
NBB75DFI	Receptacle - BNC - D style - feedthrough - iso - nickel	15.28
NAUSB	Feedthrough USB	9.40

Switchcraft

Full Switchcraft Line - Call for Price and Availability

Description	Model	Retail
Female Standard 1/4" Panel Mount	S-11	3.00
Female 1/4" Panel Mount, Extended Threading	S-11L	3.50
Female TRS 1/4" Panel Mt - Shorting Shunt	S-12A	3.50
Female Standard TRS 1/4" Panel Mount	S-12B	3.50
Female Cable Mt 1/4" Extension	S-121	11.00
Female Cable Mt 1/4" Extension, Lg Barrel	S-128	9.50
Female Cable Mt TRS 1/4" Extension	S-131	13.50
Female Thick Panel 1/4"	S-151	10.00
Female Thick Panel TRS 1/4"	S-152B	11.00
Male Mono 1/4" Right Angle Barrel Style	S-226	6.50
1 Pin Screw Type Microphone, used on our MS Series	S-2501F	6.00
Standard Male 1/4" , Disassembled, Larger Crimp	S-2P1603A	4.00
Standard Male 1/4"	S-280	4.00
Male TRS 1/4"	S-297	7.50
Female XLR, Nickel	S-A3F	7.00
Male XLR, Nickel	S-A3M	6.50
Female Miniature 3 Pin XLR	S-TA3FL	12.50
Male Miniature 3 Pin XLR	S-TA3ML	11.50
Female Miniature 4 Pin XLR	S-TA4FL	14.00
Male Miniature 4 Pin XLR	S-TA4ML	12.50

G&H ShowSavers - Male 1/4"

Made in USA

Description	Model	Retail
ShowSaver, Nickel Finish	G-BF2P	3.50
ShowSaver, Brass Finish	G-BF2P-BR	3.50
ShowSaver, 100% Gold-Plated	G-BF2P-G	7.00
ShowSaver, Large Hole, Nickel	G-BF2PL	3.50
ShowSaver, Large Hole, Brass	G-BF2PL-BR	3.50
ShowSaver, Large Hole, 100% Gold-Plated	G-BF2PL-G	7.00
USA Midsize, Nickel	G-BF2PS	5.50
ShowSaver, TRS, Nickel	G-BF3P	6.00
ShowSaver, TRS, 100% Gold-Plated	G-BF3P-G	9.50
Quiet Plug, Nickel, with Shorting Sleeve	G-BFQP	5.50
"BOSS" Banana MDP, Black or Red	G-MDP	5.50
Megafoot Jumbo, Nickel	G-MF2P	7.50
Megafoot Jumbo, Large Hole, Nickel	G-MF2PL	7.50
Rightfoot, Right Angle, Nickel	G-RF2P	6.50
Rightfoot, Right Angle, Large Hole, Nickel	G-RF2PL	6.50
Rightfoot, Right Angle, Large Hole, Brass	G-RF2PL-BR	6.50
Rightfoot, Right Angle, Large Hole, Gold-Plated	G-RF2PL-G	13.00
Rightfoot, TRS, Right Angle, Nickel	G-RF3P	8.00
Quiet Rightfoot, Right Angle w/ Shorting Sleeve	G-RFQP	8.00

Amphenol / EP

Description	Model	Retail
Amphenol 3 Pin Male Mic with Retaining Ring	91MC3M	30.00
Amphenol 4 Pin Male Mic with Retaining Ring	91MC4M	23.50
4 Pin Female Cable Mount Speaker Connector	EP-4-11P	34.00
4 Pin Male Cable Mount Speaker Connector	EP-4-12	25.00
4 Pin Female Panel Mount Speaker Connector	EP-4-13P	28.00
4 Pin Male Panel Mount Speaker Connector	EP-4-14	19.00
6 Pin Female Cable Mount Speaker Connector	EP-6-11P	41.50
6 Pin Male Cable Mount Speaker Connector	EP-6-12	26.00
6 Pin Female Panel Mount Speaker Connector	EP-6-13P	34.00
6 Pin Male Panel Mount Speaker Connector	EP-6-14	24.00
8 Pin Female Cable Mount Speaker Connector	EP-8-11P	35.00
8 Pin Male Cable Mount Speaker Connector	EP-8-12	27.50
8 Pin Female Panel Mount Speaker Connector	EP-8-13P	36.50
8 Pin Male Panel Mount Speaker Connector	EP-8-14	24.50

M Series - Professional Circular

Pins	Description	Configuration	Model	Retail
39	W1 Compatible - high density - miniature quarter turn bayonet connectors - Pre fitted Gold plated Solder contacts - Shock Proof	Female Inline	M39LF	150.00
		Male Inline	M39LM	120.00
		Female Chassis	M39PF	100.00
		Male Chassis	M39PM	110.00
61	W2 Compatible - high density - miniature quarter turn bayonet connectors - Pre fitted Gold plated Solder contacts - Shock Proof	Female Inline	M61LF	172.00
		Male Inline	M61LM	148.00
		Female Chassis	M61PF	126.00
		Male Chassis	M61PM	126.00
85	Heavy duty design - Fast and reliable bayonet locking - IP67 when mated - High quality Gold Plated contacts	Female Inline	M85LF	330.00
		Female Inline Rubber	M85LFR	390.00
		Male Inline	M85LM	270.00
		Female Chassis	M85PF	318.00
122	W3 Compatible - Hermaphroditic design - Intermateable with MASS series - Up to 40 pair cable	Female Chassis	M85PM	204.00
		Pin/Socket Inline	M122L	458.00
		Pin/Socket Chassis	M122P	370.00
150	Heavy duty design - Fast and reliable bayonet locking - IP67 when mated - High quality Gold Plated contacts - M150LFR includes rubberized locking ring	Female Inline	M150LF	454.00
		Female Inline Rubber	M150LFR	512.00
		Male Inline	M150LM	318.00
		Female Chassis	M150PF	440.00
159	VEAM - Maximum-duty Aluminum body - Shockproof High-density rubber insert - Gold-plated Pin + Socket contacts - 1/4 turn "positive" twist-lock mating - Easy-to-use alignment notches - The VR is a reverse style VEAM compatible with certain existing systems	Male Chassis	M150PM	254.00
		Female Inline	V159LF	1298.00
		Male Inline	V159LM	578.00
		Male Chassis	V159PM	558.00
176	W4 Compatible - Hermaphroditic design - Intermateable with MASS series - Up to 56 pair cable	Female Inline	VR159LF	1298.00
		Male Inline	VR159LM	578.00
		Female Chassis	VR159PF	1178.00
		Pin/Socket Inline	M176L	658.00
201	Heavy duty design - Fast and reliable bayonet locking - IP67 when mated - High quality Gold Plated contacts - Up to 67 channels	Pin/Socket Chassis	M176P	534.00
		Female Inline	M201LF	610.00
		Male Inline	M201LM	394.00
		Female Chassis	M201PF	596.00
		Male Chassis	M201PM	330.00

CA-Com Circular

Pins	Description	Configuration	Model	Retail
8	Gold plated machined contacts for quality signal path & long term reliability - Ergonomic arctic grip or rubber covered coupling nuts for ease of use with gloved hands - Most Rugged Speaker Connector Available	Female Chassis	CA8PF	38.00
		Male Chassis	CA8PM	30.00
		Female Inline	CA8LFR	118.00
		Male Inline	CA8LMR	110.00
		Female Inline Spider	CA8LFX	70.00
		Male Inline Spider	CA8LMX	78.00
19	Gold plated machined contacts for quality signal path & long term reliability - Ergonomic arctic grip or rubber covered coupling nuts for ease of use with gloved hands - Best 6 Channel Audio Disconnect Available	Female Chassis	CA19PF	42.00
		Male Chassis	CA19PM	26.00
		Female Inline	CA19LFR	124.00
		Male Inline	CA19LMR	110.00
		Female Inline Spider	CA19LFX	66.00
		Male Inline Spider	CA19LMX	80.00

Edac / Elco

Pins	Description	Configuration	Model	Retail
56	EDACON Hermaphroditic Contact Mating Design - Mating and Unmating Simplified by use of Actuating Screws - Versatile Metal Cover Design Permits Assembly or Disassembly after Cabling is Complete plus Cable Entry Style Flexibility	Actuating Screw	ED56P	19.00
		Receptacle	ED56R	17.00
		Cover	ED56C	29.00
90	Excellent Connector for Light-Duty Applications	Actuating Screw	ED90P	39.00
		Receptacle	ED90R	16.50
		Cover	ED90C	35.00
120		Actuating Screw	ED120P	43.80
		Receptacle	ED120R	43.00
		Cover	ED120C	39.00
	Spade Contacts - Gold Solder	Solder	EDGCS	0.40
	Spade Contacts - Gold Crimp	Crimp	EDCCS	0.40

Call for Other Configurations.

Instrument

Description	Shield	OD	Model	Retail
Ultimate Guitar 18ga w/ Double Shield	95% Double Serve	.270	ULT-1	0.98
Artist Instrument 20ga Blk	75% Serve	.235	GA	0.48
Belden 20ga Neoprene	75% TC Spirals	.235	B9778	1.38

Microphone

Description	Shield	OD	Model	Retail
Belden "Custom" 22ga	90% Serve	.260	ML	0.73
Artist 24ga - 6 Colors	75% Serve	.225	ML2	0.40
CBI Star Quad Conductor 24ga	95% Braid	.250	MLQUAD	0.73
Belden Ultimate 20ga - 6 Colors	90% Braid	.265	MLULT	0.88
Belden "Brilliance" Star Quad	95% Braid	.245	B1192A	1.63
Belden 110ohm AES/EBU 22ga	90% TC Brd + 100% Foil	.234	B1696A	1.23
Belden Neoprene 20ga	85% Braid	.262	B8412	1.88
Belden Studio/TT, 24ga - 104x40	Dble Spiral - "French Braid"	.176	B9397	1.63
Mogami Neglex Quad Mic 24ga	Super Flexible Serve	.236	M2534	2.23

Speaker - Round / Zip

Description	Stranding	OD	Model	Retail
16/2 Power Series, Blk w/ Blue Strp	26 x 30	.290	SC-16	0.48
14/2 Power Series, Blk w/ Yel Strp	42 x 30	.315	SC-14	0.73
12/2 Power Series, Blk w/ Wht Strp	65 x 30	.360	SC-12	0.98
10/2 Power Series, Blk w/ Red Strp	105 x 30	.420	SC-10	1.13
14/2 Zip Clear w/ Red Ground Stripe	42 x 30	.305	SCZ-14	0.45
12/2 Clear Rope Lay, Super-Flexible	262 x 37	.472	Monst-12	0.98

Video / Coax

Description	Shield	OD	Model	Retail
Belden 3 x RG59 RGB Flexible	95% Braid	.388	B1406B	2.98
Belden 5 x RG59 VGA Flexible	95% Braid	.477	B1417B	3.98
Belden Dual RG59 S-Video Round	95% Braid	.255	B1808A	2.38
Belden RG58 Solid 20ga	95% TC Braid	.193	B8240	0.60
Belden RG59 Solid 23ga	95% BC Braid	.242	B8241	0.60
RG59 Stranded 23ga	95% BC Braid	.245	C8241S	0.63
Belden RG6 Copper 18ga	Duofoil + 61% TC Braid	.270	B9248	0.70
Belden RG6 Copper/Steel 18ga	Duobond II +60% AL Braid	.270	B9116	0.38

Control / Data

Description	Shield	OD	Model	Retail
Belden 9 Cond 24ga, Gry	100% Beldfoil	.244	B9539	0.83
Belden 22ga 6 Cond, Gry	100% Foil + 65% TC Braid	.245	B9942	1.25
Belden 1 Pair 24ga DMX, Gry	100% Foil + 90% TC Braid	.232	B9841	1.20
Belden 2 Pair 24ga DMX, Gry	100% Foil + 90% TC Braid	.340	B9842	1.20
CBI 1 Pair 24ga DMX, Blk	100% Foil + 90% TC Braid	.232	C9841	0.88
CBI 2 Pair 24ga DMX, Blk	100% Foil + 90% TC Braid	.340	C9842	0.98
Belden 3 Cond 22ga, Gry	100% Beldfoil	.199	B8771	0.40
Belden / CBI CAT 5E Network	Unshielded TP	.175	B1583A	0.33
Plenum Rated CAT 5E Network	Unshielded TP	.175	B1585A	0.73
C-CAT 5E - BLUE	Unshielded TP	.175	CAT5E-BLU	0.23

Multipair Audio

Pairs	Description	OD	Model	Retail
2	Black Flexible Jkt, 100% Indiv Shld 24ga	.260	MPA-2	0.75
4	4 pair IJ , Individual Jkt and 100% shld, 24ga	.400	MPA-4IJ	1.48
6	Black Flexible Jkt, 100% Indiv Shld 24ga	.385	MPA-6	1.38
8	8 pair IJ , Individual Jkt and 100% shld, 24ga	.480	MPA-8IJ	2.48
8	Mogami Studio 8 Pair, IJ, Spiral Shield	.453	M2932	6.88
8	Mogami AES/EBU Digital IJ 8 Pair	.543	M3162	9.75
9	Belden Black Flexible Jkt, 100% Indiv Shld 24ga	.415	MPA-9	1.88
9	AES/EBU 110 ohm 100% Indiv Shld 24ga	.488	B9732	4.48
12	Belden Black Flexible Jkt, 100% Indiv Shld 24ga	.435	MPA-12	2.50
16	Black Flexible Jkt, 100% Indiv Shld 24ga	.500	MPA-16	3.38
20	Belden Blk Flexible Jkt, 100% Indiv Shld 24ga	.575	MPA-20	3.75
20	Black Flexible Jkt, 100% Indiv Shld 24ga	.575	MPA-20B	3.13
28	Belden Blk Flexible Jkt, 100% Indiv Shld 24ga	.685	MPA-28	6.25
28	Black Flexible Jkt, 100% Indiv Shld 24ga	.685	MPA-28B	4.75
32	Belden Blk Flexible Jkt, 100% Indiv Shld 24ga	.710	MPA-32	6.88
32	Black Flexible Jkt, 100% Indiv Shld 24ga	.710	MPA-32B	5.50
40	Belden Blk Flexible Jkt, 100% Indiv Shld 24ga	.815	MPA-40	8.13
40	40 pair IJ , Individual Jkt and 100% shld, 24ga	1.05	MPA-40IJ	10.00
48	Belden Blk Flexible Jkt, 100% Indiv Shld 24ga	.880	MPA-48	9.38
56	Belden Blk Flexible Jkt, 100% Indiv Shld 24ga	.950	MPA-56	10.63

Multiconductor Speaker

Pairs	Description	OD	Model	Retail
13/4	Heavy Duty 13/4 Unshielded, Black, Flexible PVC Jkt	.430	MCS-134	2.48
11/4	Heavy Duty 11/4 Unshielded, Black, Flexible PVC Jkt	.490	MCS-114	3.23
13/6	Heavy Duty 13/6 Unshielded, Black, Flexible PVC Jkt	.520	MCS-136	2.63
13/8	Heavy Duty 13/8 Unshielded, Black, Flexible PVC Jkt	.565	MCS-138	3.48
12/8	Heavy Duty 12/8 Unshielded, Black, Flexible PVC Jkt	.590	MCS-128	4.73
11/4+13/4	CBI Special Design Heavy Duty 11-4 + 13-4 SS, Blk, Flex	.720	MCS-EV	5.48
10pr+14/4	10 100% Shielded Audio Pairs + 2 14ga Spkr Lines (Pairs)	.620	MPAS-102	3.40
14pr+14/4	14 100% Shielded Audio Pairs + 2 14ga Spkr Lines	.640	MPAS-142	4.33
18pr+14/4	18 100% Shielded Audio Pairs + 2 14ga Spkr Lines	.725	MPAS-182	5.98
18pr+14/8	18 100% Shielded Audio Pairs + 4 14ga Spkr Lines	.840	MPAS-184	6.48

Installation - Colors May Vary, Specify BLK, GRY, or WHT

Cond	Shield	Description	NEC	OD	Model	Retail
22/2	100% Foil	Commercial 22/2 Twisted Pair Shielded	CL3	.142	C222S	0.23
22/2	100% Foil	Belden Standard 22/2 Audio, 6 Colors	CM	.142	B1503A	0.35
18/2	none	Commercial 18/2 Twisted Pair Unshielded	CL3	.165	C182U	0.35
16/2	none	Commercial 16/2 Twisted Pair Unshielded	CL3	.200	C162U	0.45
16/4	none	Commercial 16/4 Unshielded	CL3	.220	C164U	0.78
14/2	none	Commercial 14/2 Twisted Pair Unshielded	CL3	.250	C142U	0.68
12/2	none	Commercial 12/2 Twisted Pair Unshielded	CL3	.280	C122U	1.05
12/4	none	Commercial 12/4 Unshielded	CL3	.358	C124U	1.98
22/2	none	Plenum 22/2 Twisted Pair Unshielded	CL3P	.135	P222U	0.28
18/2	none	Plenum 18/2 Twisted Pair Unshielded	CL3P	.145	P182U	0.35
16/2	none	Plenum 16/2 Twisted Pair Unshielded	CL3P	.165	P162U	0.45
14/2	none	Plenum 14/2 Twisted Pair Unshielded	CL3P	.200	P142U	0.70
12/2	none	Plenum 12/2 Twisted Pair Unshielded	CL3P	.230	P122U	1.08
22/2	100% Foil	Plenum 22/2 TP 100% Foil Shield	CL2P	.127	P222S	0.25
14/2	100% Foil	Belden 14/2 Shielded Speaker	CL3	.265	B5100FE	0.73
22/2	100% Foil	Belden 22/2 TP 100% Foil Shield, Sml Dia	CM	.138	B8451	0.43
2 Pair	100% Foil	Belden Intercom 2 Pair, Ind Shld, Cmn Grnd	CM	.168	B8723	0.53

A Spooling Fee applies to bulk lengths requiring special spooling